

ア ン グ ル

熱間圧延品 JIS-G4317

鋼種 SUS304

BASE

円/kg

サ イ ズ					長 さ			kg/M	E X 円/kg
t	x	A	x	B	4,000 kg/本	5,000 kg/本	6,000 kg/本		
3	x	20	x	20	3.58			0.894	80
3	x	25	x	25	4.52			1.13	80
3	x	30	x	30	5.48	6.85	8.22	1.37	50
3	x	35	x	35			9.66	1.61	BASE
3	x	40	x	40	7.40	9.25	11.1	1.85	BASE
3	x	50	x	50	9.48	11.8	14.2	2.37	BASE
4	x	30	x	30			10.6	1.77	50
4	x	35	x	35			12.6	2.12	BASE
4	x	40	x	40	9.64	12.1	14.5	2.41	BASE
4	x	50	x	50	12.4	15.4	18.5	3.09	BASE
5	x	30	x	30			13.1	2.18	50
5	x	40	x	40	11.9	14.9	17.9	2.98	BASE
5	x	45	x	45			20.5	3.41	BASE
5	x	50	x	50	15.2	19.0	22.9	3.81	BASE
5	x	65	x	65			30.3	5.05	10
6	x	30	x	30			15.2	2.54	50
6	x	35	x	35			18.2	3.03	BASE
6	x	40	x	40			21.0	3.50	BASE
6	x	50	x	50	17.9	22.4	26.9	4.48	BASE
6	x	60	x	60			32.6	5.44	10
6	x	65	x	65	23.9	29.8	35.8	5.97	10
6	x	75	x	75	27.7	34.6	41.5	6.92	10
6	x	100	x	100	37.3	46.6	55.9	9.32	10
7	x	70	x	70			44.5	7.42	10
8	x	65	x	65			46.4	7.73	10
8	x	75	x	75			54.1	9.02	10
8	x	80	x	80			57.8	9.63	10
8	x	90	x	90			66.0	11.0	10
8	x	100	x	100			73.2	12.2	10
9	x	50	x	50			38.6	6.43	BASE
9	x	65	x	65			51.8	8.63	10
9	x	75	x	75	40.4	50.5	60.6	10.1	10
9	x	90	x	90			73.8	12.3	10
9		100		100			82.2	13.7	10
9	x	125	x	125			103	17.2	50
10	x	100	x	100	60.4		90.6	15.1	10
12	x	100	x	100			105	17.5	10
12	x	125	x	125			136	22.7	50
15	x	125	x	125			168	28.0	50
15	x	150	x	150			203	33.8	180

ア ン グ ル (SUS316, 316L)

熱間圧延品 JIS-G4317

鋼種 SUS316

BASE

円/kg

サ イ ズ		長 さ		kg/M	E X 円/kg
		4,000 kg/本	6,000 kg/本		
t	x A x B				
3	x 20 x 20	3.60		0.90	80
3	x 25 x 25	4.56		1.14	80
3	x 30 x 30		8.28	1.38	50
3	x 40 x 40		11.2	1.87	BASE
4	x 50 x 50		18.7	3.12	BASE
5	x 40 x 40		18.0	3.00	BASE
5	x 50 x 50		23.0	3.83	BASE
6	x 50 x 50		27.0	4.50	BASE
6	x 65 x 65		36.1	6.02	10
6	x 75 x 75		41.8	6.97	10
9	x 75 x 75		60.6	10.1	10
10	x 100 x 100		91.2	15.2	10

鋼種 SUS316L

BASE

円/kg

サ イ ズ		長 さ		kg/M	E X 円/kg
		4,000 kg/本	6,000 kg/本		
t	x A x B				
3	x 20 x 20	3.60		0.90	80
3	x 25 x 25	4.56		1.14	80
3	x 30 x 30		8.28	1.38	50
3	x 40 x 40		11.2	1.87	BASE
4	x 50 x 50		18.7	3.12	BASE
5	x 40 x 40		18.0	3.00	BASE
5	x 50 x 50		23.0	3.83	BASE
6	x 50 x 50		27.0	4.50	BASE
6	x 65 x 65		36.1	6.02	10
6	x 75 x 75		41.8	6.97	10
9	x 75 x 75		60.6	10.1	10
10	x 100 x 100		91.2	15.2	10

研 磨 ア ン グ ル

* HL品 --- 全面 #240HL仕上げ

* #400品 --- 外2面 #400研磨仕上げ


鋼種 SUS304

HL品 BASE 円/kg
#400品 BASE 円/kg

サ イ ズ							単重 kg/本	HL品		#400品	
t	x	A	x	B	x	L		EX	円/kg	EX	円/kg
3	x	20	x	20	x	4,000	3.58	80		80	
3	x	25	x	25	x	4,000	4.52	80		80	
3	x	30	x	30	x	4,000	5.48	50		50	
3	x	30	x	30	x	6,000	8.22	50		50	
3	x	40	x	40	x	4,000	7.40	BASE		BASE	
3	x	40	x	40	x	6,000	11.1	BASE		BASE	
3	x	50	x	50	x	6,000	14.2	BASE		BASE	
4	x	40	x	40	x	4,000	9.64	BASE		BASE	
4	x	40	x	40	x	6,000	14.5	BASE		BASE	
4	x	50	x	50	x	4,000	12.4	BASE		BASE	
4	x	50	x	50	x	6,000	18.5	BASE		BASE	
5	x	40	x	40	x	4,000	11.9	BASE		BASE	
5	x	40	x	40	x	6,000	17.9	BASE		BASE	
5	x	50	x	50	x	4,000	15.2	BASE		BASE	
5	x	50	x	50	x	6,000	22.9	BASE		BASE	
6	x	30	x	30	x	6,000	15.2	50			
6	x	40	x	40	x	6,000	21.0	BASE			
6	x	50	x	50	x	4,000	17.9	BASE		BASE	
6	x	50	x	50	x	6,000	26.9	BASE		BASE	
6	x	60	x	60	x	6,000	32.6	10			
6	x	65	x	65	x	4,000	23.9	10		10	
6	x	65	x	65	x	6,000	35.8	10		10	
6	x	75	x	75	x	4,000	27.7	10		10	
6	x	75	x	75	x	6,000	41.5	10		10	
6	x	100	x	100	x	6,000	55.9	10			
8	x	80	x	80	x	6,000	57.8	10			
8	x	100	x	100	x	6,000	73.2	10			
9	x	75	x	75	x	4,000	40.4	10		10	
9	x	75	x	75	x	6,000	60.6	10		10	
9	x	90	x	90	x	6,000	73.8	10			
10	x	100	x	100	x	4,000	60.4	10		10	
10	x	100	x	100	x	6,000	90.6	10		10	

コールドアングル

(ピン角コールドアングル)




鋼種 SUS304 長さ 6000mm

BASE

円/kg

サイズ				内R	4M品 kg/本	6M品 kg/本	E X 円/kg
t	x	A	x				
3	x	20	x	20	1.5 以下	3.54	80
3	x	25	x	25	1.5 以下	4.48	80
3	x	30	x	30	1.5 以下	5.44	8.16 50
3	x	40	x	40	1.5 以下	7.36	11.0 BASE
3	x	50	x	50	1.5 以下	9.24	13.9 BASE
4	x	40	x	40	1.5 以下		14.5 BASE
4	x	50	x	50	1.5 以下		18.3 BASE
5	x	30	x	30	1.5 以下		13.1 50
5	x	40	x	40	1.5 以下		17.9 BASE
5	x	50	x	50	1.5 以下		22.6 BASE
6	x	30	x	30	2.0 以下		15.5 50
6	x	40	x	40	2.0 以下		21.2 BASE
6	x	50	x	50	2.0 以下		26.9 BASE
6	x	60	x	60	2.0 以下		32.6 10
6	x	65	x	65	2.0 以下		35.5 10
6	x	75	x	75	2.0 以下		41.2 10
6	x	100	x	100	2.0 以下		55.4 10
9	x	50	x	50	2.0 以下		39.0 BASE
9	x	75	x	75	2.0 以下		60.6 10
9	x	100	x	100	2.0 以下		81.6 10

不 等 辺 ア ン グ ル



鋼種 SUS304

BASE

円/kg

サ イ ズ						断面積 (cm ²)	単重 kg/本	EX 円/kg
t	x	A	x	B	x L			
4	x	45	x	30	x 6,000	2.87	13.6	BASE
* 6	x	50	x	30	x 6,000	4.49	21.4	BASE
* 6	x	65	x	50	x 6,000	6.66	31.7	BASE
6	x	75	x	50	x 6,000	7.15	34.4	BASE
6	x	100	x	75	x 6,000	10.2	49.0	BASE
6	x	125	x	75	x 6,000	11.8	55.9	BASE
7	x	75	x	50	x 6,000	8.36	39.8	BASE
* 7	x	100	x	75	x 6,000	11.9	56.7	BASE
* 9	x	75	x	50	x 6,000	10.4	50.0	BASE
* 9	x	90	x	75	x 6,000	14.2	67.2	BASE
9	x	100	x	75	x 6,000	15.0	72.0	BASE
9	x	125	x	75	x 6,000	17.3	82.2	BASE
9	x	150	x	90	x 6,000	20.9	99.0	BASE
12	x	150	x	90	x 6,000	27.4	130	BASE

*印は切断品です。

SUS430 SUS304 フォーミングアングル SUS304 スモールアングル

フォーミングアングル SUS430 2B CG研磨品 BASE 円/kg

t	x	サイズ				L	単重 kg/本	E X 円/kg
		A	x	B	x			
2	x	20	x	20	x	4,000	2.30	125
2	x	25	x	25	x	4,000	2.92	125
2	x	30	x	30	x	4,000	3.54	70
2	x	40	x	40	x	4,000	4.76	70
3	x	20	x	20	x	4,000	3.24	10
3	x	25	x	25	x	4,000	4.24	10
3	x	30	x	30	x	4,000	5.20	BASE
3	x	40	x	40	x	4,000	7.04	BASE

フォーミングアングル SUS430 外2面#400研磨品 BASE 円/kg

t	x	サイズ				L	単重 kg/本	E X 円/kg
		A	x	B	x			
2	x	30	x	30	x	4,000	3.54	170
2	x	40	x	40	x	4,000	4.76	170
3	x	20	x	20	x	4,000	3.34	110
3	x	25	x	25	x	4,000	4.24	110
3	x	30	x	30	x	4,000	5.20	100
3	x	40	x	40	x	4,000	7.04	100


フォーミングアングル SUS304 外2面#400研磨品 BASE 円/kg

t	x	サイズ				L	単重 kg/本	E X 円/kg
		A	x	B	x			
2	x	30	x	30	x	4,000	3.64	170
2	x	40	x	40	x	4,000	4.92	170
3	x	20	x	20	x	4,000	3.44	120
3	x	25	x	25	x	4,000	4.40	120
3	x	30	x	30	x	4,000	5.32	100
3	x	40	x	40	x	4,000	7.24	100

スモールアングル(フォーミング品)SUS304 外2面HL/SPV BASE 円/kg

t	x	サイズ				L	外面R (mm)	単重 kg/本	E X 円/kg
		A	x	B	x				
1	x	9	x	9	x	4,000	1.5	0.568	280
1	x	10	x	10	x	4,000	1.5	0.632	220
1	x	12	x	12	x	4,000	1.5	0.760	190
1	x	13	x	13	x	4,000	1.5	0.824	180
1	x	16	x	16	x	4,000	1.5	1.01	130
1	x	19	x	19	x	4,000	1.5	1.20	120
1	x	25	x	25	x	4,000	1.5	1.53	180
1.2	x	19	x	19	x	4,000	2.0	1.39	100
1.2	x	25	x	25	x	4,000	2.0	1.90	90
1.2	x	30	x	30	x	4,000	2.0	2.17	90
1.2	x	32	x	32	x	4,000	2.0	2.32	70
1.5	x	30	x	30	x	4,000	2.5	2.85	20
1.5	x	32	x	32	x	4,000	2.5	3.04	BASE

フォーミングアングル



鋼種 SUS304

BASE

円/kg

サイズ						2種 0.7t R		1種 1.5t R		
t	x	A	x	B	x	L	kg/本	EX 円/kg	kg/本	EX 円/kg
2	x	20	x	20	x	4,000	2.37	100		
2	x	25	x	25	x	4,000	3.01	90		
2	x	30	x	30	x	4,000	3.64	90		
2	x	40	x	40	x	4,000	4.92	90		
3	x	15	x	15	x	4,000	2.48	90		
3	x	20	x	20	x	4,000	3.44	40		
3	x	25	x	25	x	4,000	4.40	40		
3	x	30	x	30	x	4,000	5.32	20		
3	x	30	x	30	x	6,000	7.98	20		
3	x	40	x	40	x	4,000	7.24	20		
3	x	40	x	40	x	6,000	10.9	20		
3	x	50	x	50	x	6,000			13.6	BASE
4	x	50	x	50	x	6,000			17.8	BASE
4	x	75	x	75	x	6,000			27.3	BASE
5	x	40	x	40	x	6,000			17.1	BASE
5	x	50	x	50	x	6,000			21.8	BASE
5	x	60	x	60	x	6,000			26.6	BASE
5	x	65	x	65	x	6,000			29.0	BASE
5	x	75	x	75	x	6,000			33.7	BASE
6	x	50	x	50	x	6,000			25.7	BASE
6	x	60	x	60	x	6,000			31.4	BASE
6	x	65	x	65	x	6,000			34.3	BASE
6	x	75	x	75	x	6,000			40.0	BASE

(注) 表面肌 t=2 2B t=3~ CG(BG)研磨品