

配管パイプ (TP-A・TPY-S)

鋼種 SUS304

BASE

円/kg

呼径		外径	sch5s		sch10s		sch20s		sch40s		sch80s			
A	B	mm	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M	肉厚 EX kg/M		
8	1/4	13.8			1.2 560 0.377		1.5 420 0.46			2.0 340 0.588		2.2 340 0.636		3.0 400 0.807
10	3/8	17.3			1.2 380 0.481	1.5 320 0.59	2.0 240 0.762			2.0 240 0.762		2.5 250 0.922	3.0 250 1.07	
15	1/2	21.7		1.2 310 0.613	1.5 250 0.755		2.0 190 0.981			2.5 150 1.2		3.0 100 1.4		
20	3/4	27.2		1.2 260 0.777	1.5 200 0.96		2.0 150 1.26			2.5 110 1.54		3.0 60 1.81		
25	1	34	1.2 240 0.98	1.5 150 1.21	2.0 110 1.59		2.5 80 1.96			3.0 30 2.32		3.5 60 2.66	4.0 60 2.99	
32	1 1/4	42.7	1.2 230 1.24	1.5 140 1.54	2.0 100 2.03		3.0 20 2.97			3.0 20 2.97		3.5 50 3.42	4.0 50 3.86	
40	1 1/2	48.6	1.2 210 1.42	1.5 120 1.76	2.0 70 2.32	2.5 40 2.87	3.0 B 3.41			3.0 B 3.41	3.5 20 3.93	4.0 20 4.44		5.1 100 5.53
50	2	60.5		1.5 110 2.2	2.0 70 2.91		3.0 B 4.3			3.5 B 4.97		4.0 B 5.63	5.0 40 6.91	5.5 100 7.54
65	2 1/2	76.3		1.5 110 2.79	2.0 70 3.7		3.0 B 5.48			3.5 B 6.35	4.0 B 7.2	5.0 40 8.88	5.2 40 9.21	7.0 140 12.1
80	3	89.1			2.0 70 4.34		3.0 B 6.43			4.0 B 8.48	5.0 40 10.5	5.5 50 11.5		7.6 140 15.4
90	3 1/2	101.6		2.0 80 4.96			3.0 B 7.37			4.0 B 9.72	5.0 30 12.0	5.7 50 13.6		8.1 160 18.9
100	4	114.3		2.0 80 5.59			3.0 B 8.32			4.0 B 11.0	5.0 30 13.6	6.0 30 16.2		8.6 160 22.6
125	5	139.8		2.0 150	3.0 10 10.2		3.5 B 11.9	4.0 B 13.5		5.0 20 16.8		6.6 60 21.9		9.5 200 30.8
150	6	165.2			3.0 10 12.1		3.5 B 14.1	4.0 B 16.1		5.0 20 20.0	6.0 30 23.8	7.1 60 28.0		11.0 200 42.3
175	7	190.7			3.0 50 14.0			4.0 40 18.6			6.0 50 27.6			
200	8	216.3			3.0 30 15.9		4.0 20 21.2	5.0 20 26.3	6.0 30 31.4	6.5 60 34.0		8.2 120 42.5		12.7 200 64.4
250	10	267.4		3.0 80 19.8	3.5 70 23.0		4.0 70 26.2	5.0 70 32.7	6.0 70 39.1	6.5 100 42.2		9.3 180 59.8		15.1 250 94.9
300	12	318.5		3.0 90 23.6	4.0 80 31.3		4.5 80 35.2		6.0 80 46.7	6.5 100 50.5		10.3 180 79.1		17.4 250 131.0
350	14	355.6			4.0 40 35.0		5.0 B 43.7	6.0 B 52.3		8.0 20 69.3		11.1 100 95.3		19.0 150 159.0
400	16	406.4		4.0 40 40.1	4.5 B 45.1		5.0 B 50.0	6.0 B 59.8	6.5 20 64.7	8.0 20 79.4		12.7 100 125.0		
450	18	457.2		4.0 40 45.2	4.5 20 50.7		5.0 20 56.3	6.0 20 67.4		8.0 40 89.5		14.3 120 158.0		
500	20	508		4.0 80 50.2	5.0 80 62.6		5.5 60 68.8	6.0 60 75.0		9.5 80 118.0		15.1 120 185.0		
550	22	558.8			5.0 100 69.0		5.5 80 75.8	6.0 80 82.6		9.5 120 130.0		15.9 150 215.0		
600	24	609.6			5.5 80 82.8	6.0 80 90.2	6.5 100 97.7			9.5 120 142.0		17.5 150 258.0		
650	26	660.4			5.5 100 89.7	6.0 100 97.8	8.0 100 130.0			12.7 150 205.0		17.5 150 280.0		
700	28	711.2			5.5 120 96.7	6.0 120 105.0	8.0 120 140.0			12.7 170 221.0		17.5 170 302.0		

配管パイプ (TP-A・TPY-S)

SUS316 BASE 円/kg

鋼種 SUS316/316L

SUS316L BASE 円/kg

呼径			外径		sch5s		sch10s		sch20s		sch40s		sch80s					
A	B	mm	肉厚	EX	肉厚	EX	肉厚	EX	肉厚	EX	肉厚	EX	肉厚	EX				
			kg/M		kg/M		kg/M		kg/M		kg/M		kg/M					
8	1/4	13.8									2.0	340		3.0	400			
											0.592				0.812			
10	3/8	17.3					1.5	320	2.0	240			3.0	250				
							0.594		0.767				1.08					
											2.0	240						
											0.767							
15	1/2	21.7					1.5	250	2.0	190			3.0	100				
							0.76		0.988				1.41					
											2.5	150						
											1.2							
20	3/4	27.2					1.5	200	2.0	150			3.0	60				
							0.966		1.26				1.82					
											2.5	110						
											1.55							
25	1	34					2.0	110					3.5	60	4.0	60		
							1.60						2.68	3.01				
											3.0	30						
											2.33							
32	1 1/4	42.7					2.0	100	3.0	20			3.5	50	4.0	50		
							2.04		2.99				3.44	3.88				
											3.0	20						
											2.99							
40	1 1/2	48.6					2.0	70	3.0	B			4.0	20		5.1	100	
							2.34		3.43				4.47			5.56		
											3.0	B						
											3.43							
50	2	60.5					2.0	70	3.0	B			4.0	B		5.5	100	
							2.93		4.32				5.67			7.58		
											3.5	B	4.0	B	5.0	40	5.2	40
											5.0		7.25	8.94	9.27			
65	2 1/2	76.3			1.5	110	2.0	70	3.0	B			3.5	B	4.0	40	5.2	40
					2.81		3.73		5.51				6.39	7.25	8.94	9.27		
80	3	89.1			2.0	70			3.0	B			4.0	B		5.5	50	
90	3 1/2	101.6			2.0	80			3.0	B			4.0	B				
					4.99				7.42				9.79					
100	4	114.3			2.0	80			3.0	B			4.0	B		6.0	30	
					5.63				8.37				11.1			16.3		
125	5	139.8			3.0	10			3.5	B	4.0	B	5.0	20		6.6	60	
									12.0	13.6			16.9			22.0		
150	6	165.2			3.0	10			3.5	B	4.0	B	5.0	20		7.1	60	
									14.2	16.2			20.1			28.1		
200	8	216.3			3.0	30			4.0	20			6.5	60		8.2	120	
									21.3				34.2			42.8		
250	10	267.4			3.0	80			4.0	70			6.5	100		9.3	180	
					19.9				26.5				42.5			60.2		
300	12	318.5			3.0	90	4.0	80	4.5	80			6.5	100		10.3	180	
					23.7	31.5			35.4				50.8			79.6		
350	14	355.6			4.0	40			5.0	B			8.0	20		11.1	100	
									43.9				69.7			95.9		
400	16	406.4			4.0	40			5.0	B			8.0	20		12.7	100	
					40.4				50.3				79.9			125.0		

TP-A(6φ ~ 318.5φ) JIS G3459
 TPY-S(355.6φ ~ 711.2φ) JIS G3468

配管パイプ

鋼種 SUS304

BASE

円/kg

外径 mm	t 1.0	t 1.2	t 1.5	t 2.0	t 3.0
	EX	EX	EX	EX	EX
	kg/M	kg/M	kg/M	kg/M	kg/M
6	1,400				
	0.125				
8	1,060				
	0.174				
10	800		700	630	
	0.224		0.318	0.399	
10.5	800	750	700	630	
	0.237	0.278	0.336	0.423	
12	700		550	500	
	0.274		0.392	0.498	
12.7	660		580	450	
	0.291		0.418	0.533	
13	630				
	0.299				
15			500		
			0.504		
16	490		350	320	
	0.374		0.542	0.697	
18	490				
	0.423				
19	490		350	270	
	0.448		0.654	0.847	
20	490		350	270	
	0.473		0.691	0.897	
25		320	250	190	
		0.711	0.878	1.15	
25.4		320	250	190	110
		0.723	0.893	1.17	1.67
30			200	150	60
			1.06	1.39	2.02
32			200	150	60
			1.14	1.49	2.17
38			150	110	30
			1.36	1.79	2.62
40				110	
				1.89	
50.8			120	70	B
			1.84	2.43	3.57